


| TRANSFORMER WEIGHT & VOLUME | | |
|-------------------------------------|----|------|
| CORE AND WINDING | kg | 2570 |
| TANK AND FITTING | kg | 970 |
| COOLING LIQUID VOLUME | L | 1265 |
| COOLING LIQUID WEIGHT | kg | 1030 |
| TOTAL TX WEIGHT | kg | 4540 |
| ADDITIONS TO THE TRANSFORMER WEIGHT | | |
| RN2c RMU WEIGHT | Kg | 500 |

| 1000kVA ELECTRICAL RATINGS | | | | | |
|-------------------------------------|---|---|-------------------------------|---------------------------------|---------|
| No Load Voltage Ratio at Normal Tap | HV Tappings | Vector Group | Frequency | Full-Load Current at Normal Tap | |
| 11000 / 415V | +7.5 to -5.0% in 2.5% INCREMENTS | Dyn11 | 50Hz | HV Side | LV Side |
| Design Impedance at Normal Tap | No Load Losses at rated Voltage & Frequency | Full Load Losses at rated Current & at 75°C Temp. | Temp. Rise above Ambient 40°C | | |
| 4.75% | 450W | 6630W | in Oil by Therm. | in Wdg. by Res. | |
| | | | 60°C | 65°C | |

| ITEM | QTY | DESCRIPTION |
|------|-----|--|
| 15 | 2 | DETACHABLE RADIATORS with AIR-RELEASE & DRAIN PLUG (520W x 1100C x 35 x 40P) |
| 14 | 1 | DRAIN VALVE (25NB) with MALE PLUG |
| 13 | 4 | JACKING PADS |
| 12 | 1 | RATING & DIAGRAM PLATE (SS) |
| 11 | 4 | TRANSFORMER LIFTING LUGS |
| 10 | 1 | OFF-CIRCUIT TAP SWITCH (6-Position & Padlockable) |
| 9 | 2 | THERMOMETER POCKET (3/4" BSP MALE THREAD) |
| 8 | 1 | OIL FILLING PIPE WITH FLANGED COVER |
| 7 | 1 | TOP COVER with LIFTING LUGS (x2) |
| 6 | 1 | OIL LEVEL GAUGE (with 15°) COLD OIL LEVEL MARK |
| 5 | 1 | AIR VENT PIPE (3/4") FOR DEHYDRANT BREATHER |
| 4 | 2 | EARTHING TERMINAL (FLAT TYPE suitable for M12 Bolt) |
| 3 | 1 | TRANSFORMER BASE (SKID TYPE) c/w HAULAGE HOLES & BRACING |
| 2 | 1 | LV CABLE BOX - 1.1kV, 4-POLE, AIR INSULATION, (FACING-'F', BS:2562) SUITABLE FOR 2 x 1c CABLES PER PHASE & N - MAX. 630mm.sq |
| 1 | 1 | HV RMU - 11kV, 200A, GCB, 630A BUS [Schneider RN2c-T1/21] x PROTECTION, (FACING-'E' BS:2526) |

ESSENTIAL LABELS

- ITEM 10 TAP CHANGER WARNING LABEL
- ITEM 6 COLD COOLANT LEVEL
- ITEM 2 LV WARNING LABEL
- ITEM 1 HV WARNING LABEL



GENERAL NOTES

- ALL DIMENSIONS ARE IN 'mm'.
- ALL DIMENSIONS/WEIGHTS ARE SUBJECT TO ± 10% TOLERANCE.
- ELECTRONIC SCALE - 1:1 (ONLY WRITTEN DIMENSIONS TO BE FOLLOWED).
- TOLERANCE ON IMPEDANCE PER IEC:60076.
- PAINT SHADE.: 632 AS PER BS:381C (SEMI GLOSS) TO ISO12944 - MIN C4 SPEC.
- O/ALL DIM IS SUBJECT TO EQUIPMENT DOOR OPENING DISTANCES

IF IN DOUBT - ASK. REMOVE ALL SHARP EDGES. DO NOT SCALE. DRAWING NOT TO SCALE

| REV | REV BY | VERIFIED | APPROVED | DESCRIPTION |
|-----|--------|----------|----------|-------------|
| | | | | |

| REVISION DESCRIPTION | REV | PROJECT |
|----------------------|-----|-------------|
| ORIGINAL | 00 | CUSTOMER |
| | | S.O. NUMBER |
| | | P.O. NUMBER |
| | | W.O. NUMBER |

| DRAWING TITLE | |
|---|--|
| GENERAL ARRANGEMENT DRAWING FOR 1000kVA WILSON e3 ECOTRANS ULTRA LOW LOSS 11000/415V, 50Hz, Dyn11, ONAN/KNAN AL WOUND DISTRIBUTION TRANSFORMER RN2c RMU | |

Wilson Power Solutions Ltd.
 Westland Square, Leeds,
 West Yorkshire LS11 5SS, United Kingdom
 Tel: +44 (0) 113 271 7588
 Fax: +44 (0) 113 277 5124
 web: www.wilsonpowersolutions.co.uk email: info@wilsonpowersolutions.co.uk

DRAWN BY: S. MALLETT DATE: 09/10/2019 DRG NO: **WPS-E3-1000-AL-A001**